



Retention Tether -Load Master



- **One inch hollow core webbing-load bearing (18Kn or 4000lbs)**
- **Marine grade bungee**
- **Two Locking or non-locking carabineer (30Kn or 6700lbs)**
- **69E twisted thread**
- **Total weight 10oz.**
- **Bar tacking for all stitched construction**

Designed to be used by DoD, Law Enforcement or civilian personnel operating aboard transport Aircraft, fixed wing or helo, and fast attack vehicles. The HRS/LM functions as a safety tether to insure that the user does not suffer a fatal fall from the aircraft or vehicle during operations. The HRS/LM is manufactured in 12, 18, 36 and 45-inch lengths (these lengths are the non-expanded lengths), NWL can and will provide built frame and use.

NWL uses bar tacking machines to insure strength at all stitched connection points and construction. The internal bungee allows for expansion and contraction of the tether, free movement of the user and the luxury of tangle free movement.

National Warrior League
nationalwarriorleague.com

| | | | |
|--------------|--------------|--|----------------|
| R & D/ Sales | Marc Shen | mshen@nationalwarriorleague.com | (727) 798-5659 |
| Admin/ Sales | Josh Wiseman | jwiseman@nationalwarriorleague.com | (207) 329-3672 |
| CS / Billing | Anne Defalco | adefalco@nationalwarriorleague.com | |